


LCW long arm series

High speed, Cylinder bed, Large vertical axis hook, Compound feed and walking foot, Reverse stitch, Lockstitch machines




LCW-28BL-20

Variety

LCW-28BL-20 20inch long arm

LCW-28BL-30 30inch long arm



Applications

- For sewing medium to heavy weight fabrics, leather, synthetics, canvas and various coated and laminated materials.
- Suitable for sewing tubular and curved work such as shoes boots, bags, handbags, filters and ducting.





LCW long arm series

Features

- Semi-automatic lubrication system.
- Large vertical axis hook.
- Safety clutch prevents the hook from being damaged.
- Reverse stitching.

Specifications (LCW-□)

Variety		28BL-20	28BL-30	
Number of needle		Two needle		
Max. sewing speed		1,500 s.p.m.	1,300 s.p.m.	
Max. stitch length		1/4" (6.2 mm)		
Clearance under presser foot	by pedal	35/64" (14 mm)		
	by hand	21/64" (8.5 mm)		
Needle bar stroke		1-5/16" (33.2 mm)		
Needle(standard)		DPx17 (#22) , 135x17 (#140)		
Thread		#8 (standard)		
Hook		Large vertical axis hook		
Amount of lift of walking foot		7/64"-7/32" (2.7 - 5.5 mm) s	standard 1/8" (standard 3.2 mm)	
Thread take up lever		Slide type		
Lubrication		Semi-automatic lubrication type		
Cylinder size		3-7/64"(79 mm) dia.		
,		20"x 4-21/64"	30"x 4-21/64"	
Working spa	100	(508 x 110 mm)	(762 x 110 mm)	
Motor		Clutch motor		
Net weight(Head only)		50Kg	65Kg	

NOTE: (1) Speed depends on threads, materials and type of operation

Needle gauge list (LCW-□)

Variety	Needle gauge size
28BL-20, 28BL-30	1/4"(6.4 mm), 5/16"(7.9mm), 3/8"(9.5mm), 1/2"(12.7mm), standard : 1/4"(6.4 mm)



SEIKO SEWING MACHINE CO., LTD.

2-13-6, Sakaecho, Funabashi-shi Chiba Prefecture, 273-0018, Japan

Phone: +81-47-420-3561 (Overseas dept.)

Fax: +81-47-420-3560

E-mail: export@seiko-sewing.co.jp

Printed in Japan 2015.08

⁽²⁾ Specifications subject to change without notice